

CHAdEMO - 1.0.0

- Specification Task Team

Member (1)

TOYOTA, NISSAN, MMC, FHI,
TAKAOKA, HASETEC, TAKASAGO, NITTETU,
TEPCO (2)

Collaborator (3)

YAZAKI, TUV-JPN, etc.

(1) as of 2010.12

(2) secretary

(3) depending on the technical topic on a work meeting

- 1st active period and goal

August 2010 – March 2011

2010-12-31 : draft document of CHAdEMO-1.0.0

- Maintenance and improvement of the specification document
- Additional requirement, including EMC and etc.

Topics - 1

- EMC

- Emission ⁽¹⁾ and Immunity

- ⁽¹⁾ Including disturbance level for RF equipments, Intelligent key and Cardiac pacemaker

- Sequence circuit

- Voltage tolerance on the 12V power supply unit

- Additional resistor to the 'charge permission and prohibition' line and the 'verification of connector connection' line

- Specification of resistor values

- Specification of minimum current of contactor 'd1', 'd2' and opt-coupler 'j'

- Coordination of control units

- Shutdown sequence ⁽²⁾ of Inverter circuit and 12V power supply unit in case of power outage and etc.

- ⁽²⁾ Power outage -> INV off -> 12V power supply (for EV relay) off -> 'd1', 'd2' off

Topics - 2

- Issues on the overvoltage category and Lightning surge protection
- CAN
 - Bit sample point
 - The difference between measured value (Voltage, Current) and value on CAN data due to delay of processing inside charger.
- Simplification of the time-out compliance specification
 - change from the ‘band-type time-compliance’ to the ‘point-type time-compliance’
- Change the error code name of vehicle CAN ID102.5.2
 - Present : ‘ other vehicle fault’
 - Modified : ‘ system error ‘
- Improvement of documentation
 - Readability of text, software flowchart and data table
 - Clarification of hardware requirements; such as AC-ground fault detection and interaction device, ground wiring, connector-lock monitoring device and etc.